

Consumer Type NiMH Low Self Discharge(LSD) Cell List

Model	Nominal capacity (mAh)	Dimensions(mm)		Standard charge		Rapid charge		Approx weight (g)
		Height	Diameter	Current (mA)	Time(h)	Current (mA)	Time (h)	
TM-LSD-AA1800	1800	50.5 (+0/-1.5)	14.5 (+0/-0.7)	180	16	900	2.4	26
TM-LSD-AA1900	1900	50.5 (+0/-1.5)	14.5 (+0/-0.7)	190	16	950	2.4	27
TM-LSD-AA2000	2000	50.5 (+0/-1.5)	14.5 (+0/-0.7)	200	16	1000	2.4	28
TM-LSD-AA2100	2100	50.5 (+0/-1.5)	14.5 (+0/-0.7)	210	16	1050	2.4	29
TM-LSD-AA2200	2200	50.5 (+0/-1.5)	14.5 (+0/-0.7)	220	16	1100	2.4	30
TM-LSD-AA2300	2300	50.5 (+0/-1.5)	14.5 (+0/-0.7)	230	16	1150	2.4	31
TM-LSD-AA2400	2400	50.5 (+0/-1.5)	14.5 (+0/-0.7)	240	16	1200	2.4	32
TM-LSD-AA2500	2500	50.5 (+0/-1.5)	14.5 (+0/-0.7)	250	16	1250	2.4	33
TM-LSD-AAA750	750	44.5 (+0/-1.5)	10.5 (+0/-0.7)	45	16	375	2.4	12.5
TM-LSD-AAA800	800	44.5 (+0/-1.5)	10.5 (+0/-0.7)	80	16	400	2.4	13
TM-LSD-AAA850	850	44.5 (+0/-1.5)	10.5 (+0/-0.7)	85	16	170	7.0	13.5
TM-LSD-AAA900	900	44.5 (+0/-1.5)	10.5 (+0/-0.7)	90	16	180	7.0	14
TM-LSD-D8000	8000	61.5 (+0/-2.0)	33.0 (+0/-1.0)	800	16	1600	7.5	146
TM-LSD-D9000	9000	61.5 (+0/-2.0)	33.0 (+0/-1.0)	900	16	1800	7.5	155