

Standard Industrial Nickel Metal Hydride (NiMH) Cell List

TM Model	Voltage (V)	Capacity		Dimensions		Standard Charge		Rapid Charge		Wt.
		Typical	Min.	Height	Dia.	mA	hour	mA	Minute	gram
		mAh	mAh	mm	mm					
AAA70	1.2	700	660	44.0±0.5	10.0+0.4	70	15	700	72	11.5
AAA80	1.2	800	750	44.0±0.5	10.0+0.5	80	15	400	140	12
AAA85	1.2	850	800	44.0±0.5	10.0+0.5	85	15	400	150	12.5
2/3AA60	1.2	600	570	28.5±0.5	13.8+0.5	60	16	600	72	13
4/5AA120	1.2	1200	1150	42.5±0.5	13.8+0.5	120	16	1200	72	21
AA60	1.2	600	600	48.5±0.5	13.8+0.5	60	16	600	72	15
AA70	1.2	700	670	48.5±0.5	13.8+0.5	70	16	700	72	17
AA100	1.2	1000	950	48.5±0.5	13.8+0.5	100	16	1100	72	20
AA120	1.2	1200	1150	48.5±0.5	13.8+0.5	120	16	1200	72	22
AA140	1.2	1400	1350	48.5±0.5	13.8+0.5	140	16	1400	72	24
AA160	1.2	1600	1550	48.5±0.5	14.0+0.5	160	16	1600	72	25.5
AA180	1.2	1800	1750	49.0±0.5	14.0+0.5	180	16	900	140	27
AA200	1.2	2000	1950	49.0±0.5	14.0+0.5	200	15	1000	140	28.5
AA220	1.2	2200	2100	49.0±0.5	14.0+0.6	220	15	1100	140	29.5
2/3A120	1.2	1200	1150	28.5±0.5	16.5+0.5	120	16	1200	72	19.5
2/3A150	1.2	1500	1450	29.5±0.5	16.5+0.5	150	15	750	140	21
4/5A180	1.2	1800	1750	42.5±0.5	16.5+0.5	180	16	1800	72	31
4/5A200	1.2	2000	1950	42.5±0.5	16.5+0.5	200	16	1000	140	33
4/5A220	1.2	2200	2100	42.5±0.5	16.5+0.5	220	15	1100	140	34
A210	1.2	2100	2050	49.5±0.5	16.5+0.5	210	16	1050	140	36
A240	1.2	2400	2300	49.5±0.5	16.5+0.5	240	16	1200	140	39
A260	1.2	2600	2500	49.5±0.5	16.5+0.5	260	16	1300	140	41
4/3A280	1.2	2800	2750	66.5±0.5	16.5+0.5	280	16	1400	140	46
4/3A350	1.2	3500	3400	66.5±0.5	16.5+0.5	350	15	1750	140	52
4/3A360	1.2	3600	3500	66.5±0.5	16.5+0.5	360	15	1800	140	53
4/3A380	1.2	3800	3650	66.5±0.5	16.5+0.5	380	14	1140	230	56
65AF400	1.2	4000	3950	64.5±0.5	18.0+0.5	400	16	2000	140	59
67AF420	1.2	4200	4100	66.5±0.5	18.0+0.5	420	15	2100	140	61.5
4/5SC220	1.2	2200	2100	33.5±0.5	22.0+0.6	220	15	1100	140	47
4/5SC240	1.2	2400	2300	33.5±0.5	22.0+0.6	240	15	1200	140	47
SC250	1.2	2500	2450	42.5±0.5	22.0+0.6	250	16	1250	140	53
SC300	1.2	3000	2950	42.5±0.5	22.0+0.6	300	16	1500	140	56

TM Model	Voltage (V)	Capacity		Dimensions		Standard Charge		Rapid Charge		Wt.
		Typical	Min.	Height	Dia.	mA	hour	mA	Minute	gram
		mAh	mAh	mm	mm					
SC330	1.2	3300	3250	42.5±0.5	22.0+0.6	330	16	1650	140	60
SC360	1.2	3600	3500	42.5±0.5	22.0+0.6	360	16	1800	140	62
C400	1.2	4000	3850	49.0±0.5	25.0+0.6	400	16	2000	140	80
C500	1.2	5000	4800	49.0±0.5	25.0+0.6	500	16	2500	140	86
D600	1.2	6000	5900	60.0±0.5	32.0+0.6	600	16	3000	140	120
D800	1.2	8000	7600	60.0±0.5	32.0+0.6	800	16	4000	140	155
D900	1.2	9000	8600	60.0±0.5	32.0+0.6	900	15	4500	140	165
F1200	1.2	12000	11000	89.0±0.5	32.0+0.6	1200	15	2400	360	230
F1400	1.2	14000	13000	89.0±0.5	32.0+0.6	1400	15	2800	360	245